

3M Double Sided Foam Tape

Features

3M™ Double Coated Urethane Foam Tape 4026 is a thick, double-coated, open-cell urethane foam tape with a paper liner.

Technical Information

Adhesive Type	3M™ High Temperature Acrylic Adhesive 100, Acrylic
Brand	3M™
Carrier Material	Urethane
Elongation at Break	100
Industries	General Industrial, Metalworking, Signage, Transportation
Overall Length (METRIC)	5 Meter
Overall Thickness (METRIC)	1.58 mm
Overall Width (METRIC)	12.7 mm
Primary Liner	62# Densified Kraft Paper
Primary Line Colour	Green Plaid
Product Form	Roll
Shelf Life in months (from date of manufacture)	24
Substrate 1	Metal (Aluminum - Powder Coated - Copper - Stainless Steel - Zinc/Galvanized)
Substrate 2	Metal (Aluminum - Powder Coated - Copper - Stainless Steel - Zinc/Galvanized)
Temperature Resistance – Initial	380 Degree Fahrenheit / 193 degrees Celsius
Tensile Strength (METRIC)	1240 kg

Distributors & Agents for Rubber, Foam & Matting Supplies

- ✓ Self Adhesive Sealing Tape
- ✓ Insertion, Neoprene & Nitrile Rubber
- ✓ Commercial Matting
- ✓ Door & Boot Rubber Seals
- ✓ Grip Products



- ✓ Auto & Marine: Matting/Carpets/Vinyl
- ✓ Latex & Foam Mattresses
- ✓ Foam Cut to Size
- ✓ Marine Fender & Hatch Seals