



99 Aumuller Street Cairns Qld 4870 **Ph 07 4035 5899** Fax 07 4035 5177 sales@jenkinsrubber.com.au www.jenkinsrubber.com.au

5060 Series PVC Nitrile Foam Tape

Features

The 5060 series is a closed-cell PVC Nitrile foam tape. It will seal from water, dust, and acts as a sound dampener. It is highly tear and abrasion resistant. The foam compresses easily and recovers its shape quickly. It has good resistance to high temperatures and weathering.

Technical Information

Backing Material	Closed-cell PVC Nitrile Foam
Colours	Black
Adhesive Type	Acrylic
Adhesive Power	6N/25mm
Foam Density	91kgs/m³
Elongation	100%
Tensile Strength	73.5N/25mm
Temperature Resistance	-10°C to 80°C
Thermal Conductivity	0.27btu/in.
Flammability (ASTM D1692-74)	Flame Retardant and Self-Extinguishing
Water Tightness	100% at <10% compression
Water Absorption (ASTM D1056-73)	6% (by weight)

Distributors & Agents for Rubber, Foam & Matting Supplies

- ✓ Insertion, Neoprene & Nitrile Rubber
- ✓ Commercial Matting
- ✓ Door & Boot Rubber Seals
- ✓ Grip Products



- ✓ Foam Cut to Size
- ✓ Marine Fender & Hatch Seals